





RoHS Compliant



PC Layout (Top View)

LED Designation :

Code	Forward	Reverse	Code	Forward	Reverse
G	Green	---	4	Yellow	Red
Y	Yellow	---	5	Green	Yellow
R	Red	---	6	Yellow	Green
O	Orange	---	9	Red	Green
3	Green	Red	0	Red	Yellow


SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min. 500V DC. for 1 minute.
 Contact Resistance : 30milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 150V AC.
 Dielectric Voltage : 1,000 Vrms at 1MA 60 Sec. Min.

2. Physical char.

Housing (Option) : For Waving Soldering Process
 PBT Glass Filled (UL 94V-0), Soldering Temperature: 245°C for 5 Sec.
 Nylon (UL 94V-0), Soldering Temperature: 260°C for 5 Sec.
 Color : Black Color
 Spring Wire :
 0.35mm Thickness Phosphor bronze Gold Plating Over Nickel
 Shielded : Brass Plating Nickel
 Temperature Range : - 40°C / +85°C
 Durability : 750 Mating cycles Min.



ALLSUN CORPORATION
 9FL,NO.292 SEC.7 CHENG TEH ROAD.TAIPEI TAIWAN.
 E - mail Address : allsun@globalsources.com

TITLE **RJ45 2X1 8 POSITIONS**
DOUBLE DECK GANG SHIELDED JACK WITW LED
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
AJ-091-21-F-XX-N1-XX

SCALE SIZE DWG. NO. 9791S SERIES

DWG. NO.	NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
AST091A02-1	THIRD ANGLE PROJECTION	LINEAR	.00±0.01 .000±0.005 .0000±0.002	.00±0.25 .000±0.13 .0000±0.05	Steven CK'D John APP'D	MAY-31 '13 MAY-31 '13
	MM INCH	ANGLE +0° 30'	RADII	+0.45 -0.15	Billy	MAY-31 '13